



Thermo
systems

Building System
SOLUTIONS

Your Trusted Parts Provider for Fully-Stocked, Quality HVAC Products.

Main: (630) 693-0930 | Parts Hotline: (630) 693-0920 | 1424 Sherman Rd, Romeoville, Illinois 60446

Panasonic WhisperGreenSelect™ VENTILATION FAN

Benefits:

- Custom, all-in-one fan and fan/LED light combo
- Pick-A-Flow speed selector – one fan, you choose the CFM
- Unique **Plug 'N Play** modules
- Revolutionary DC motor ensures optimal CFM output
- GU24 base LED lamps provide **energy efficient** illumination
- Flex-Z Fast™ bracket provides **swift installation**
- Comply with ASHRAE, LEED, Cal-Green and ENERGY STAR
- And more!

FV-05-11VKS1, FV-05-11VK1, FV-11-15VK1



FV-05-11VKS1, FV-05-11VK1, FV-11-15VK1



As Easy As 1-2-3!

1

Select a Base Fan Model

Built-in Pick-A-Flow™ speed selector allows you to select your required airflow with the flip of a switch

2

Select Value Added Features

- Multi-Speed w/Time Delay
- Condensation Sensor
- NiteGlow™ LED Night Light
- SmartAction® Motion Sensor

3

Install with the Flex-Z Fast™ System

Uniquely designed installation bracket provides flexible and easy installation for new construction or renovation projects.



Product ID	Description
VTX400P	Atmosphere Corded Centrifugal In-line Fan with Integrated Pressure Switch, 175 CFM at 0.2 s.p., for high static pressure applications and long duct runs, 4" duct, backdraft damper not included, speed controller available separately
VTX600	Atmosphere Corded Centrifugal In-line Fan, 465 CFM at 0.2 s.p., for high static pressure applications and long duct runs, 6" duct, backdraft damper not included, speed controller available separately
VTX800	Atmosphere Corded Centrifugal In-line Fan, 681 CFM at 0.2 s.p., for high static pressure applications and long duct runs, 8" duct, backdraft damper not included, speed controller available separately
VTX400	Atmosphere Corded In-line Fan, 200 CFM at 0.2 s.p., for high static pressure applications and long duct runs, 4" duct, backdraft damper not included; speed controller available separately
S-600	Atmosphere Corded Mixed-Flow In-line Fan, 312 CFM at 0.2 s.p., 6" duct, sealed casing, compact design, backdraft damper included, speed controller available separately
FV-0709VB1	EcoVent® Fan, 70/90 CFM, 0.7/1.5 sone, ENERGY STAR®-qualified, 2x6 construction, production builders/ manufactured housing
EZSV14	EZSoffitVent™ Soffit Termination System, for ventfans up to 110 CFM using 4" ducting
PC-RD05C5	FlexDamper™ Ceiling Radiation Damper for Combustible and Non-Combustible Assemblies; for WhisperGreen® Select, WhisperCeiling®DC, WhisperSense®DC, WhisperFit®DC, WhisperValue®DC
FV-10VEC2	Intelli-Balance®100 Corded Any Climate Energy Recovery Ventilator (ERV), 50/60/70/80/90/100 CFM for exhaust and supply, occupant-controlled boost function; MERV 8 filter included, ASHRAE 62.2 timing function, 4" or 6" duct
FV-10VEC2R	Intelli-Balance®100 Mirrored and Corded Any Climate Energy Recovery Ventilator (ERV), 50/60/70/80/90/100 CFM for exhaust and supply, occupant-controlled boost function; for residential, single-family installations with mirrored floor plans; MERV 8 filter
FV-WC10VE1	Wall Cap, Double chambers for 100 CFM exhaust and 100 CFM supply air; for WhisperComfort®60, Intelli-Balance® 100, Intelli-Balance®200
FV-0511VQ1	WhisperCeiling®DC Fan, 50/80/110 CFM, <0.3/<0.3/<0.3 sone, ENERGY STAR®-qualified, 2x8 construction
FV-0511VQL1	WhisperCeiling®DC Fan/Dimmable LED Light & Night-light, 50/80/110 CFM, <0.3/<0.3/0.4 sone, ENERGY STAR®-qualified, 2x8 construction
FV-0511VF1	WhisperFit®DC Fan, 50/80/110 CFM, <0.3/<0.3/0.8 sone, ENERGY STAR®-qualified, 2x6 construction, repair & remodeling
FV-0511VFL1	WhisperFit®DC Fan/Dimmable LED Light, 50/80/110 CFM, <0.3/<0.3/0.4 sone, ENERGY STAR®-qualified, 2x6 construction, repair & remodeling
FV-CSVK1	WhisperGreen®Select Condensation Sensor Module
FV-0511VKS3	WhisperGreen®Select Dual Speed Fan, high speed 50/80/110 CFM, low speed 30-100 CFM for continuous operation, <0.3/<0.3/<0.3 sone, ENERGY STAR® Most Efficient-qualified, 2x8 construction,
FV-0511VKSL3	WhisperGreen®Select Dual Speed Fan/Dimmable LED Light & Night-light, high speed 50/80/110 CFM, low speed 30-100 CFM for continuous operation, <0.3/<0.3/<0.3 sone, ENERGY STAR® Most Efficient-qualified, 2x8 construction, New!
FV-MSVK1	WhisperGreen®Select Motion Sensor Module
FV-1115VK3	WhisperGreen®Select Single Speed Fan, high speed 110/130/150 CFM, <0.3/<0.3/<0.3 sone, ENERGY STAR® Most Efficient - qualified, 2x8 construction New!
FV-0511VK3	WhisperGreen®Select Single Speed Fan, high speed 50/80/110 CFM, <0.3/<0.3/<0.3 sone, ENERGY STAR® Most Efficient - qualified, 2x8 construction New!
FV-1115VKL3	WhisperGreen®Select Single Speed Fan/Dimmable LED Light & Night-light, high speed 110/130/150 CFM, <0.3/<0.3/0.4 sone, ENERGY STAR® Most Efficient -qualified, 2x8 construction, New!
FV-0511VKL3	WhisperGreen®Select Single Speed Fan/Dimmable LED Light & Night-light, high speed 50/80/110 CFM, <0.3/<0.3/<0.3 sone, ENERGY STAR® Most Efficient -qualified, 2x8 construction, New!
FV-VS15VK1	WhisperGreen®Select Variable Speed Module
FV-0810VSS1	WhisperValue®DC Dual Speed Fan, high speed 50/80/100 CFM, low speed down to 30 CFM for continuous operation, <0.3/0.4/0.9 sone, ENERGY STAR®-qualified, 2x4 construction, ceiling or wall mount, multi-family
FV-0510VSL1	WhisperValue®DC Fan/Dimmable LED Light & Night-light, 50/80/100 CFM, <0.3/0.4/0.9 sone, ENERGY STAR®-qualified, 2x4 construction, multi-family
FV-0510VS1	WhisperValue®DC Single Speed Fan, high speed 50/80/100 CFM, <0.3/0.4/0.9 sone, ENERGY STAR®-qualified, 2x4 construction, ceiling or wall mount, multi-family



Romeoville Warehouse
1424 Sherman Rd,
Romeoville, IL 60446




Elmhurst Parts Store
960 Industrial Dr., Unit 1
Elmhurst, IL 60126



Main: (630) 693-0930
Parts Hotline: (630) 693-0920



[linkedin.com/company/thermosystems/](https://www.linkedin.com/company/thermosystems/)



Scan QR code to visit our
website:
www.thermohvac.com